

ELECTRIC CHARACTERISTICS

Nominal voltage	400 Vac (480 Vac or additional voltage available upon request)
Frequency	50/60 Hz
Regulation	Independent
Core type	Square section linear
Input	Asymmetric

FINSTCA	Rated Power (KVA)	Rated Current (A)	Voltage Variation (%)	Response Time (ms/V)	Output Accuracy (±%)	Dimensions (mm) a x b x h	Weight Kg	Case
FINSTCA.1535.A55	55	79	+ 15%, -35%	6	± 1	1100X650X1800	590	4
FINSTCA.1535.B85	85	123	+ 15%, -35%	11	± 1	1100X650X1800	790	4
FINSTCA.1535.C120	120	173	+ 15%, -35%	11	± 1	1100X1100X1800	950	4
FINSTCA.1535.D175	175	253	+ 15%, -35%	16	± 1	1100X650X1800	1150	4
FINSTCA.1535.E240	240	346	+ 15%, -35%	12	± 1	2 units 1100x1100x1800	1700	4 (2u)
FINSTCA.1535.F345	345	498	+ 15%, -35%	17	± 1	2 units 1100x1100x1800	1980	4 (2u)
FINSTCA.1535.G440	440	635	+ 15%, -35%	16	± 1	4 units 1100x1100x1800	3300	4 (4u)
FINSTCA.1535.H550	550	794	+ 15%, -35%	18	± 1	4 units 1100x1100x1800	4400	4 (4u)
FINSTCA.1535.I800	800	1155	+ 15%, -35%	20	± 1	4 units 1100x1100x1800	5400	4 (4u)

CASE 4
